


HSF



SPECIFICATIONS

Insulation Resistance: $5\text{M}\Omega$ Min
Contact Resistance: $3.0\text{m}\Omega$ Max
Withstand Voltage: DC 300V, 10S
The Cable Assembly Must 100% Test

Ordering Information

C9130 - xx 01 xxx 101

No. of Pins: 02~15P Shape Style: 01=one end Process, another one end plate tin Length of Line

CONNECT METHOD

P1	Color	P2
01	XXX	OPEN
02	XXX	OPEN
03	XXX	OPEN
	●●●●●●●●	
XX	XXX	OPEN

Wire SPEC	LENGTH	TOLERANCE
ULxxxx 22~28AWG	1~499	±5
	500~999	±10
	1000~1500	±15
	1501~3000	±20
	3001~5000	±30
	5001~	± Lx1%

③	WF2502-TPSN01	Terminal	PH2.50mm Phosphor Bronze Tin Terminal	xx	PCS
②	WF2502-HxxE01	Housing	PH2.50mm xxP BEIGE Housing	1	PCS
①	Wxxxx-1xxx00001	WIRE	UL: xxxx, AWG: 22~28, Color: xx, Wire	xxxx	MM
NO.	PART NO.	NAME	Specification	Q'TY	UNIT

					工程图 ENGINEERING		绘图 DRAW	BEN	09/09/24	SCALE	FREE	WCON 维峰五金电子有限公司 WAFE HARDWARE ELECTRONICS CO. LTD	
					X.X	±0.30	设计 DESIGN			UNIT	mm		
					X.XX	±0.20	审 核 CHECK			SIZE	A4	料号 PART NO.	C9130-xx01xxx101
A0	09/09/24	NEW	_____	_____	X.XXX	±0.10				SHEET	1/1	品名 TITLE:	PH2.50 **P Housing TO OPEN
版次 REV	日期 DATE	变 更 说 明 MODIFICATION DESCRIPTION	变 更 CHANGE	核 准 APPROVE	Angle DIM	± 2° TOL	核 准 APPROVE			PROJ.		客户料号Customer NO.	