



HSF



SPECIFICATIONS

Insulation Resistance: 5M Ω Min
Contact Resistance: 3.0 Ω Max
Withstand Voltage: DC 300V, 10S
The Cable Assembly Must 100% Test

Ordering Information

C9130 - xx 01 xxx 601

No. of Pins:
02~25P

Shape Style:
01=one end Process,
another one end plate tin

Length of Line

CONNECT METHOD

P1 Color P2
01 XXX OPEN
02 XXX OPEN
03 XXX OPEN
XX XXX OPEN

Wire SPEC	LENGTH	TOLERANCE
ULxxxx 22~28AWG	1~499	±5
	500~999	±10
	1000~1500	±15
	1501~3000	±20
	3001~5000	±30
	5001~	± Lx1%

③	WF2508-TPSN01	Terminal	PH2.50mm Phosphor Bronze Tin Terminal	xx	PCS
②	WF2508-HxxW01	Housing	PH2.50mm xxP White Housing	1	PCS
①	Wxxxx-1xxx00001	WIRE	UL: xxxx, AWG: 22~28, Color: xx, Wire	xxxx	MM
NO.	PART NO.	NAME	Specification	Q' TY	UNIT

工程图 ENGINEERING	绘图 DRAW	BEN	09/09/26	SCALE	FREE	WCON 维峰五金电子有限公司 WAFE HARDWARE ELECTRONICS CO. LTD	
X.X	±0.30	设计 DESIGN		UNIT	mm		
X.XX	±0.20	审核 CHECK		SIZE	A4	料号 PART NO.	C9130-xx01xxx601
X.XXX	±0.10	核准 APPROVE		SHEET	1/1	品名 TITLE:	PH2.50 **P Housing TO OPEN
Angle	± 2'			PROJ.	客户料号 Customer NO.		
DIM	TOL						

版次 REV	日期 DATE	变更说明 MODIFICATION DESCRIPTION	变更 CHANGE	核准 APPROVE
A0	09/09/26	NEW		